



CESARE COLOSIO SPA

Via Alessandrini, 14 - 25086 Rezzato - Brescia
Tel +39-030-2592161 Fax +39-030-2792643
Email: info@colosio.it www.colosio.it



CESARE COLOSIO SPA



HT-25

Single-cylinder machine for the production of man, woman and baby socks in two feeds

Production features:

- 2 FEEDS terry + 5 colours motif on the same course
- 1 feed terry + 10 colours motif on the same course
- 2 FEEDS plain sock with 5 colours per course motif
- 1 feed plain sock with 10 colours per course motif
- 2 colours jacquard in 2 FEEDS
- 2 colours filet stitch in 2 FEEDS
- tri-dimensional on plain or terry sock + tri-dimensional in the welt
- 3 ground changes with their plating changes on the same sock
- Tri-dimensional rings and hooks

Technical features:

- No mechanical change from plain to terry
- Production of 3 different articles alternatively
- Fast heel and toe without picker
- Adjustable speed of the cutter saw

Optional:

- Suction fan
- Yarn break sensors
- Yarn tension controlling device (general yarn, rubber and plating yarn)
- Software (Windows 7/8 compatible)
- Socks turner
- Anti-twist, Dream

HT-25



Macchina Monocilindro a 2 CADUTE ,a controllo elettronico integrale, per la produzione di calze da uomo, donna e bambino.

Caratteristiche produttive:

- Calza in spugna a 2 CADUTE + 5 colori per rango
- Calza in spugna a 1 caduta + 10 colori per rango
- Calza e collant in maglia liscia a 2 CADUTE + disegno a 5 colori per rango
- Calza e collant in maglia liscia a 1 caduta + disegno a 10 colori per rango
- Vero jacquard in 2 colori a 2 CADUTE
- Filet stitch in 2 colori a 2 CADUTE
- Tridimensionale su maglia liscia o spugna
- Tridimensionale nel polsino
- Calza con 3 cambi di fondo e rispettivo cambio di vanisè
- Spugna disegnata con 5 colori
- Asole tridimensionali e anelli di aggancio

Caratteristiche tecniche:

- Passaggio da spugna a maglia liscia senza alcuna modifica meccanica
- Ciclo alternato per produrre 3 diversi articoli consecutivamente (destra, sinistra e tascello)
- Punta e tallone senza picker
- Velocità variabile della seghetta

Diameter HT-25	3 3/4"
Needles count	From 120 240
FEEDS HT-25	2SPEED
SPEED RPM	260
CONSUMPTION WITH SUCTION FUN KW	1,50
CONSUMPTION WITHOUT SUCTION FUN KW	0,80

Optional

- Ventola per aspirazione
- Sensori rottura filato
- Dispositivi per il controllo della tensione dei fili (Fondo, vanisè, elastico)
- Software disegni (Windows 7/8)
- Rovesciatore
- Anti-twist, Dream

